



## TECHNICAL DATA SHEET

### AMBER GLOSS EMULSION

<b>PRODUCT DESCRIPTION</b>	Amber Gloss Emulsion is a pure acrylic emulsion based paint with high quality pigments, having excellent durability and long lasting gloss retention with non yellowing property for exterior applications. It has very good alkali resistance with excellent water resistance. It is highly washable and has very low dirt pick up property. It has very good leveling and opacity. It contains anti fungal and anti bacterial additives.
----------------------------	--

<b>RECOMMENDED USES</b>	Amber Gloss Emulsion is mostly suitable for the high gloss water based decorative requirements for interior or exterior applications of concrete, plaster, gypsum, brickwork, wood, masonry work etc. It provides a low odour high gloss finishes with long durability mostly suitable for the application of the area having less ventilation and exhausts. It can be used for Amber Ecosystem Topcoat also.
-------------------------	---

### TECHNICAL DATA

<b>COLOUR, DRY FILM</b>	As per the Amber Shade Card
<b>FINISH, DRY FILM</b>	Smooth / Glossy
<b>VOLUME SOLIDS (ASTM D2697)</b>	40 ± 2%
<b>SPECIFIC GRAVITY</b>	1.17 ± 0.05 (For white and pastel colours)
<b>THEORETICAL SPREADING</b>	10 – 8 M <sup>2</sup> /LTR
<b>RECOMMENDED DFT (DRY FILM)</b>	40 – 50 Microns / Coat
<b>RECOMMENDED WFT (WET FILM)</b>	100 – 125 Microns / Coat
<b>FLASH POINT</b>	Water Base



## TECHNICAL DATA SHEET

### DRYING TIME

Drying time @ 30°C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time).	
<b>TOUCH DRY</b>	1 hour
<b>DRY TO RECOAT</b>	4 – 6 hours
<b>HARD DRY</b>	24 hours

### ADVANTAGES

<b>AMBER GLOSS EMULSION</b>	Excellent durability, excellent UV & weather resistance, very good anti chalking property, long lasting gloss with non yellowing property, very good leveling and opacity, highly washable and very low dirt pick up, and low odour glossy coating.
-----------------------------	---

### APPLICATION INSTRUCTION

<b>SURFACE PREPARATION</b>	Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.
----------------------------	---

### APPLICATION DATA

<b>APPLICATION METHOD</b>	Roller, Brush or Spray
<b>CLEANING/THINNING</b>	Water
<b>THINNER (VOLUME)</b>	Water Max 10 % depends on method of application
<b>CONV. SPRAY REQUIREMENTS</b>	Possible
<b>AIRLESS SPRAY REQUIREMENTS</b>	Pressure: 2100 psi
<b>NOZZLE SIZE</b>	0.018” – 0.021”
<b>MIXING RATIO (BY VOLUME)</b>	NA
<b>POT LIFE @ 30°c (100 ml)</b>	NA



## TECHNICAL DATA SHEET

### SYSTEM

<b>RECOMMENDED SYSTEM</b> To be applied on prepared surface.	Amber Acrylic Primer (W.B.)	1 coat
	Amber Gloss Emulsion	2 coats
	Leveling the surface (if required)	
	Amber Stucco Filler (For Interior)	2 coats
	Amber Shield Exterior Filler (For Exterior)	2 coats

### ADDITIONAL DATA

<b>SHELF LIFE @ 30°C</b>	18 months, in original sealed container, with proper storage conditions.
--------------------------	--

### HEALTH & SAFETY

<b>SAFETY PRECAUTIONS</b>	<p>Generally, most of the water base paints are quite safe to handle with due precautions. As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. s Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area. Local safety regulations to be followed</p>
---------------------------	--



## TECHNICAL DATA SHEET

### STORAGE & HANDLING

<p><b>STORAGE</b></p>	<p>Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not stock paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.</p>
-----------------------	---