



TECHNICAL DATA SHEET

AMBER N.C. WOOD STAIN

PRODUCT DESCRIPTION	A decorative color stain based on Nitrocellulose Resin which gives a transparent wood color, weather resistant and durable.
----------------------------	---

RECOMMENDED USES	On wooden surfaces.
-------------------------	---------------------

TECHNICAL DATA

COLOUR, DRY FILM	As per shade card.
Viscosity (25°C)	30 - 35 sec
SPECIFIC GRAVITY	0.93 ± 0.02
Solid by Weight %	18 ± 3 %
Covering Capacity	15 m ² /Lit.
Flash Point	8°C

DRYING TIME

Drying time @ 30°C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time).	
TOUCH DRY	10 - 15 min
DRY TO RECOAT	30 - 45 min.

APPLICATION INSTRUCTION

SURFACE PREPARATION	Surface should be dry, clean and free from dust.
----------------------------	--

APPLICATION DATA



TECHNICAL DATA SHEET

APPLICATION METHOD	Brush or spray.
CLEANING/THINNING	Amber Thinner 121 or Amber Special Thinner

ADDITIONAL DATA

SHELF LIFE @ 30°C	24 months, in original sealed container, with proper storage conditions.
--------------------------	--

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none">- Ensure good ventilation during application and drying.- Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.- Keep out of reach of children.
---------------------------	--

STORAGE & HANDLING

STORAGE	The product must be stored according to Amber Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed
----------------	---