



**TECHNICAL DATA SHEET**

**AMBER N.C. PRIMER SURFACER**

<b>PRODUCT DESCRIPTION</b>	N.C. Primer Surfacer is a special primer based on nitrocellulose and alkyd resins. The product has been designed to have optimum balance between sandibility, water resistance and hold out of the topcoat.
----------------------------	---

<b>RECOMMENDED USES</b>	Special primer for nitrocellulose system application. Suitable for wooden furniture work, steel surfaces, for automobiles.
-------------------------	--

**TECHNICAL DATA**

<b>COLOUR, DRY FILM</b>	White and Grey
<b>FINISH, DRY FILM</b>	Smooth / Matt
<b>VOLUME SOLIDS (ASTM D2697)</b>	44 ± 2%
<b>SPECIFIC GRAVITY</b>	1.32 ± 0.05
<b>THEORETICAL SPREADING</b>	12.5 – 10 M2 /LTR
<b>RECOMMENDED DFT (DRY FILM)</b>	35 – 45 Microns/Coat
<b>RECOMMENDED WFT (WET FILM)</b>	80 – 100 Microns/Coat
<b>FLASH POINT</b>	7°C

**DRYING TIME**

Drying time @ 30°C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time).	
<b>TOUCH DRY</b>	15 – 30 minutes
<b>DRY TO RECOAT</b>	3 – 4 hours
<b>HARD DRY</b>	4 – 5 hours



**TECHNICAL DATA SHEET**

**ADVANTAGES**

<b>AMBER N.C. PRIMER SURFACER</b>	Quick drying, excellent sandability, good water resistance, better hold out of topcoat, easy to apply.
-----------------------------------	--

**APPLICATION INSTRUCTION**

<b>SURFACE PREPARATION</b>	Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.
----------------------------	---

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Roller, Brush or Spray
<b>CLEANING/THINNING</b>	Amber Lacquer Thinner
<b>THINNER (VOLUME)</b>	10 – 15% depends on method of application
<b>CONV. SPRAY REQUIREMENTS</b>	Possible
<b>AIRLESS SPRAY REQUIREMENTS</b>	Pressure : 2000 – 2300 psi
<b>NOZZLE SIZE</b>	0.017” – 0.021”
<b>MIXING RATIO (BY VOLUME)</b>	One pack
<b>POT LIFE @ 30°c (100 ml)</b>	NA



## TECHNICAL DATA SHEET

### SYSTEM

<b>RECOMMENDED SYSTEM</b> To be applied on prepared surface.	Amber N.C. Primer Surfacer	1 coat
	Amber N.C. Putty or Polyester Putty	2 coats
	Amber N.C. Primer Surfacer	1 coat
	Amber N.C. Auto Lacquer Topcoat	1 coat

### ADDITIONAL DATA

<b>SHELF LIFE @ 30°C</b>	18 months, in original sealed container, with proper storage conditions.
--------------------------	--

### HEALTH & SAFETY

<b>SAFETY PRECAUTIONS</b>	<p>As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area. This product contains flammable materials and should be kept away from the sparks and open flames, smoking in the area should not be permitted. Local safety regulations should be followed</p>
---------------------------	--

### STORAGE & HANDLING



#### TECHNICAL DATA SHEET

<p><b>STORAGE</b></p>	<p>Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not stock paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.</p>
-----------------------	---