



**NATIONAL<sup>®</sup>**  
**PAINTS**



**SYNTHETIC ENAMEL**



809 OFF WHITE




375 PEACH MELBA




820 MAGNOLIA



385 TANGO



811 BUTTER CREAM



810 BROKEN WHITE



818 JONQUIL



395 CLEMENTINE



816 MUSHROOM



812 PALE CREAM



345 LEMON



721 TOP TOPAS



819 DARK CREAM



815 CREAM



348 YELLOW




349 OLD CAT



# أصباغ ناشونال الزيتية (سنتك انامل) Synthetic Enamel Paints



292 DYRO GREY




293 SILVER GREY




294 FLAKE GREY




295 MINERVA GREY



880 CORAL PINK



888 CAPRICE



777 PETAL PINK



870 WILD LILAC



350 CATERPILLAR



743 GOLDEN BROWN



690 CHASSIS RED



752 CHOCOLATE



630 TOP ORANGE




670 VERMILION



650 POST RED




757 MAROON




404 CHIFFON BLUE



444 BERMUDA BLUE



511 BRILLIANT GREEN



517 TURQOISE



455 TROPEZ BLUE



482 SUMMER BLUE



487 STEEL BLUE



512 NAPOLI GREEN



420 SKY BLUE



413 PERIWINKLE



296 CHARCOAL



555 NOBLE GREEN



440 ROYAL BLUE



460 MARINA BLUE



581 GROTTA



578 MICHEL GREEN





# NATIONAL<sup>®</sup> PAINTS

## Description:

National Synthetic Enamel Paints are specially developed to provide superior interior and exterior protection. It is based on alkyd resins and contains pigments, additives etc.

## Characteristics:

- Tough, durable and weather resistant.
- Has good flow and gloss retention.
- Gives smooth glossy, semi glossy and matt finish.
- High Coverage.

## Recommended Use:

It is recommended for use on metal, wood, and concrete surfaces and is also suitable for painting heavy equipments and vehicles.

## Theoretical Spreading Rate:

14 m<sup>2</sup> / litre depending on application method, nature of surface, film thickness etc.

## Application Method and Thinning:

Roller, brush or spray. For thinning add 5-15% National G.P Thinner/National Q.D Thinner (depending on application method and the product).

## Touch Dry (Minimum):

Synthetic Enamel Gloss I (6 hours),  
Synthetic Enamel Gloss II (2-3 hours),  
Eco Enamel (3 hours),  
Industrial Quick Dry Enamel (5-10 minutes),  
Flatt/Matt Synthetic Enamel-Interior (1 hour).

## Note:

For further information, please refer to National Technical Data Sheets.

## الوصف:

أصباغ ناشونال الزيتية (سنثتك انامل) هي أصباغ طورت خصيصاً لإعطاء حماية فائقة داخلية وخارجية. مكونة من راتينجات ألكيدية، وتحتوي على مواد ملونة ومواد مضافة لتحسين خواص الصبغ.

## المميزات:

- المتانة، قوة التحمل والمقاومة العالية للتقلبات الجوية.
- انسيابية جيدة مع الإحتفاظ باللمعان.
- تعطي سطحا أملسا (لامع، نصف لمعة ومطفي).
- تغطية عالية.

## الإستعمالات:

ينصح باستعمالها على الأسطح المعدنية، الخشبية والخرسانية كما أنه ملائم لطلاء المعدات الثقيلة والسيارات.

## معدل التغطية النظري:

١٤ م<sup>٢</sup> / لتر يعتمد على طريقة الاستعمال، طبيعة السطح وسماكة طبقة الصبغ الخ.

## طريقة الاستعمال والتخفيف:

يمكن استخدامها بواسطة الفرشاة، الرول أو مسدس الرش. يخفف بنسبة ٥ - ١٥ ٪ مع ناشونال جي بي ثنر / ناشونال كويك دراى ثنر (يعتمد ذلك على طريقة الإستعمال ونوع المنتج).

## الجفاف عند اللمس (كحد أدنى):

سنثتك انامل جلوس ١ (٦ ساعات)،  
سنثتك انامل جلوس ٢ (٢ - ٣ ساعات)،  
ايكو انامل (خال من الرصاص) - (٣ ساعات)،  
كويك دراى انامل صناعي (٥ - ١٠ دقائق)،  
فلات / مات سنثتك انامل - داخلي (١ ساعة).

## ملاحظة:

ولمزيد من المعلومات، يرجى الرجوع الى المواصفات الفنية لمنتجات أصباغ ناشونال.





**NATIONAL<sup>®</sup>**  
**PAINTS**

[www.nationalpaints.com](http://www.nationalpaints.com)