

National Spray Paints

DESCRIPTION	A modified acrylic-based aerosol paint that is specially formulated for decorative and protective purposes. It is suitable for both interior and exterior surfaces.
RECOMMENDED USE	<ul style="list-style-type: none"> - Ideal for decorative purposes. - Ideal for use on metal, timber and paper surfaces. - Fluorescent color: It is a striking eye-catcher for used on traffic signs, car and ship signboards, signs for firefighting vehicles, facilities and other safety notices.

TECHNICAL INFORMATION

COLOR	Solid, Metallic, Fluorescent colors.
FINISH	Gloss & Matt
SOLID BY WEIGHT %	17 ± 2 % by weight
VISCOSITY (25°C)	11-12 sec
COVERAGE RATE	0.8 – 1.6 m ² per 400 CC
TOUCH DRY	Within 10 minutes.
HARD DRY	Within 30 minutes.

SURFACE PREPARATION

The surface must be clean and dry, free from grease and oil prior to the application. Sand to improve adhesion.

APPLICATION DATA

SPRAY APPLICATION	<ul style="list-style-type: none"> - Shake the container vigorously for at least 30 seconds before use. - Hold the can approximately 30 cm from the surface to be sprayed on. - While spraying, keep the can in horizontal motion so that coating is deposited evenly, do not permit paint to build up. - Spray several thin coats, instead of one heavy coat, and allow each coat to cure for at least 10 minutes. - For Fluorescent range, the surface must be white-based, to bring out the fluorescent effect.
--------------------------	---

CLEANING	After spraying, turn the can upside down, point the spray nozzle into the refuse can or old paper and press the spray head for approximately 2 seconds to clear the paint in the valve. If necessary, the spray head can be cleaned by pulling out of the valve opening.
STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months, in original sealed container, with proper storage conditions.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Container is filled under pressure, kept away from sunlight and heat above 50°C, sparks and open flame. - Do not puncture or incinerate even when the container is empty. - Avoid spraying into eyes, skin and inhalation. - In case of contact with eyes, flush repeatedly with water and contact the physician immediately.
TDS ISSUE NO. & DATE	(1) - July 2017

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.