

SAITEX SPRAY PAINT WHITE 800

DESCRIPTION

Aerosol Spray Paint White is fast dry one component acrylic base topcoat which is used on variety of sanded metal and non metal surfaces directly. It provides excellent adhesion, good covering and smooth finish to the substrates. It can be used on various substrates like wood, metals, plastic, automotive and equipment etc.

TYPICAL PROPERTIES

Color Dry film	White
Finish Dry film	Glossy
Specific Gravity (ISO 2811-1)	0.96 ± 0.02
Application Viscosity	13±1 sec
Dry film thickness (DFT)	15 – 20 microns
Drying Time	10-15 min.
Flash off time between coats	1-2 min.
No. Of Coats	2-3
Recommended time for Topcoat	60 min.

RECOMMENDED USES

- As a topcoat for multiple metal surfaces, furniture articles and wooden parts, booth interiorly and exteriorly where glossy finish required.

ADVANTAGES

- Fast Drying.
- Non-yellowing, non-fading, weather resistant.
- Low consumption and high spreading rate.
- Provide maximum performance.
- Provide smooth finishing to substrates.

PACKAGING SIZE

- 400 ml

SURFACE PREPARATION

- The surface need to apply shouldbe cleaned properly.
- Surface should be free of any dirt, grease, moisture and oil.
- Sand the surface if it is glossy and then clean it gently for proper application.

CERTIFICATIONS

- Certificates are available upon request

APPLICATION METHOD

- Aerosol Spray Paint White is fast drying ready to use paint that should be applied on cleaned surface. Applying surface should be free of any grease, dirt, rust, moisture, loose paint or any other material.
- If surface is glossy, sand the surface gently before application.
- Protect that area which is near to the spraying part by some cloth or paper properly to avoid any kind of mist.
- Shake the can vigorously for 50-60 seconds before use and also shake in between the coat for smooth and uniform application.
- Point opening/actuator of the spray button toward the object, holding the can at the distance of 16-20 cm from surface to be painted. Press spraying button/actuator firmly.
- 2-3 thin coats are recommended according to the requirements instead of one heavy coat that may cause sagging.
- For recoating, it is recommended to wait for 60 minutes and then sand properly for further application.
- Saitex Spray Paint White can be applied on primer as well as directly to the substrate keeping in mind all the recommended precautions.

SAFETY PRECAUTIONS

- Avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc.
- Eyes: In the event of accidental splashes, flush eye with water immediately and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water or approved industrial cleaner.
- Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion seek medical attention immediately.
- In the event of ingestion and eye contact, seek medical attention immediately.
- Painting must be carried out in well-ventilated area.
- Local safety regulations need to be followed.

STORAGE & SHELF LIFE

- Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near to any ignition sources.
- Closed the cap of the can immediately after the spraying and also clean the actuator every time before spray to have smooth finish
- Handle with care.
- Stir well before use.
- Shelf life at 30°C is 36 months in original sealed container with proper storage conditions.