

## DIXIE SYNTATIC ENAMEL PAINT

<b>DESCRIPTION:</b>	High quality Alkyd base paint, lead free, high gloss, excellent durability long lasting quick drying, excellent color and gloss retention, yellowing resistance, high coverage rate, excellent adhesion to the painted surface
<b>RECOMMENDED USE:</b>	Interior and Exterior applications, suitable for metal, wood and masonry surfaces.

### TECHINCAL INFORMATION:

Color	As per color card
Finish	Smooth glossy finish
Specific Gravity	1.05-1.2 gm/ml
Weight of Solids	65-70%
Coverage Rate	5-12 m <sup>2</sup> /Lt (depending on color)
Drying Time	Touch dry: 3-5 Hrs. Recoatible: 6-8 Hrs. Full Dry: 8-16 Hrs.
Flash Point	37°-45° C

### SURFACE PREPERATION:

Surface should be clean, dry and free of oil.
---

### APPLICATION DATA:

Application Method:	Brush, Roller , Spray
Thinning, cleaning of tools	10-20% white Spirit
GUIDING DATA FOR AIRLESS SPRAY:	Nozzle Tip: 0.015"-0.020" Pressure at 2200 PSI.
Film Thickness	(D.F.T. ) 30μ (W.F.T. ) 60μ

### MISCELLANEOUS DATA:

STORAGE	The product should be stored in a cool and well-ventilated place, protected from heat and direct sun. Containers should keep tightly closed.
Handling	MIX well before use.
Shelf Life	24 Months.
Safety & Health	Avoid contact skin and eyes. Wear Eye protector Keep out of reach Children