

DULUX ART DECOR



Product Name	Dulux Art Decor			
Description and Usage	<p>Dulux Art Decor is a textured emulsion paint suitable for interior and exterior application. This product contains high quality aggregates which enables the painter to create a wide range of texture effects. It will cover minor surface imperfections and is capable of hiding hairline cracks. Dulux Art Decor is a tough weather resistant texture coating which contains anti-fungal & anti-bacterial additives & has excellent alkali resistance for longer lasting walls.</p> <p>Dulux Art Decor is suitable on new or previously painted surfaces such as cement plaster, concrete, block work, rendered surfaces, gypsum board etc.</p>			
Benefits	<ul style="list-style-type: none">• Excellent weather resistance• Excellent alkali resistance• Anti-fungal & Anti-bacterial properties• Easy application & creates a wide range of texture effects• Hides minor surface imperfections and hairline cracks			
Pack Size	18 Litre			
Colour Range	White and shades			
Film Properties				
Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surface.			
Composition (nominal)	Binder : Acrylic copolymer Solvent : Water			
Product Data				
Finish	Grooved Texture / Matt			
Volume Solids %	69 ± 2%			
Typical WFT (microns) per coat	1450 – 1650 µm			
Typical DFT (microns) per coat	1000 – 1140 µm			
Theoretical Coverage	0.7 – 0.6 m²/ litre / coat			
Practical Spreading Rate	Depending on substrate, application method, application conditions and system, etc.			
Specific Gravity	White 1.90 ± 0.05 kg/l			
Drying / Over coating Information	° C	Touch Dry	Overcoating	Hard Dry
	@ 30°C	1 - 2 hrs	6 - 8 hrs	24 hrs
Application	Trowel			
Thinning				
Trowel	Ready for use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).			

DULUX ART DECOR



Cleaning Up

Clean all equipment with water immediately after use.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.

System Information

New, Normal, Sound Surfaces

Surface preparation

Dulux Acrylic Primer (1 coat)

Topcoat

Dulux Art Decor (1 coat)

Health, Safety and Environment Information

Product Safety Data Sheet available upon request.

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.

11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.