

DULUX TEX



Product Name	Dulux Tex		
Description and Usage	<p>Dulux Tex is a weather resistant texture paint available in fine, medium or heavy texture finish. It is suitable for use on interior or exterior surfaces. It will cover minor surface imperfections and capable of hiding hairline cracks. Dulux Tex has excellent alkali resistance, anti-fungal & anti-bacterial properties for longer lasting walls.</p> <p>Dulux Tex is suitable on new or previously painted surfaces such as cement plaster, concrete, block work, rendered surfaces, gypsum board etc.</p>		
Benefits	<ul style="list-style-type: none">• Excellent weather resistance• Excellent alkali resistance• Anti-fungal & anti-bacterial properties• Available in fine, medium or heavy texture finish• Hides minor surface imperfections and hairline cracks		
Pack Size	18 Litre		
Colour Range	White and colours		
Film Properties			
Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surface.		
Composition (nominal)	Binder	: Acrylic copolymer	
	Solvent	: Water	
Product Data			
Finish	Fine Texture / Matt	Medium Texture / Matt	Heavy Texture / Matt
Volume Solids %	62 ± 2%	64 ± 2%	64 ± 2%
Typical WFT (microns) per coat	250 – 800 µm	230 – 800 µm	500 – 1000 µm
Typical DFT (microns) per coat	150 – 480 µm	147 – 512 µm	320 – 640 µm
Theoretical Coverage	4.1 – 1.3 m²/ L / coat	4.30 – 1.2 m²/ L / coat	2 – 1 m²/ L / coat
Specific Gravity	White 1.72 ± 0.05 kg/l	White 1.73 ± 0.05 kg/l	White 1.80 ± 0.05 kg/l
Practical Spreading Rate	Depending on substrate, application method, application conditions and system, etc.		
Drying / Over coating Information	° C @ 30°C	Touch Dry 1 - 2 hrs	Overcoating 6 - 8 hrs Hard Dry 24 hrs
Application	Roller, Brush, Spray, Trowel or Scraper		
Thinning			
Brush or Roller	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).		
Spray	For normal use thinning is not usually necessary, but if required add up To but if required add up to 1 part of clean water to 10 parts of paint (10%)		

Spray Recommendations

Spray

Gravity Feed Hopper gun or other suitable equipment

Cleaning Up

Clean all equipment with water immediately after use.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.

System Information

New, Normal, Sound Surfaces

Surface preparation

Dulux Acrylic Primer (1 coat)

Topcoat

Dulux Tex
(2 coats of Fine / Medium
OR 1 coat of Heavy)

Health, Safety and Environment Information

Product Safety Data Sheet available upon request.

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.