

PLASTO PRIMER



Description:

Plasto Primer is a fast drying, plastic adhesion primer which improves the adhesion of subsequently applied paint system on plastic car parts.

Features:

- Easy to apply.
- Suitable for use on all plastic and fiber car body parts.
- Good adhesion.
- Good Durability and Flexibility.

Technical Information:

Composition	Special resins – Solvent – Additives
Drying Time	10 – 15 min At 20 °C
Dust resistance time	30 min

Pre-treatment:

- Old or original paintwork well sanded and cleaned.
- Clean the surface well.
- Spray two coats of Plasto Primer without dilution.
- Allow 5 - 10 min flash-off time between coats.

For Professional Use Only

VR Technical Data Sheet No. EN/Plasto Primer



Product Preparation / STD Application :

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.		
	New surfaces: Surface must be sanded and cleaned by suitable Degreaser. Old surfaces: As recommendation in Pre-treatment.		
	Mixing Ratio: Ready for use without any additions.		
	Pot life at 25°C: 8 hrs.		
	Apply the film immediately after mixing, avoiding air entrapment.		
	<table border="1"> <tr> <td>25°C</td><td>15 – 20 mins</td></tr> </table>	25°C	15 – 20 mins
25°C	15 – 20 mins		
	Short wave: 3-4 Minutes		

Storage and Packaging:

STORAGE	Must be stored in dry space provided with adequate ventilation at 25°C & 65% R.H.
PACKING	1 L.
Shelf life	2 years at adequate ventilation and relative humidity.

For Professional Use Only

VR Technical Data Sheet No. EN/Plasto Primer