



Technical Data Sheet

Yacht PU Clear Varnish Exterior

Product Code - F65**** Series

F65**** - Yacht PU Clear Varnish Exterior

Type	Yacht Varnish is a high quality varnish with a UV filter for exterior use. It provides a surface that is resistant to wear and the effects of the sea.
Salient Features	<ul style="list-style-type: none"> - UV filter - Provides easy long term maintenance - Resistant to wear and saline atmosphere
Field of Application	Can be used for all exterior wood work where a clear finish is required above classic
Application	Brush / Spray / Roller
Available packing	1 Ltr and 1 USG

Technical Information	
Solid contents (by Wt.)	55 ± 2%
Specific gravity (25 °C)	0.9 ± 0.02 Kg/Ltr.
Viscosity	70 ± 5 Sec (FC B4 @ 25°C) – Glossy , Silk matt, 18 ± 1 (Emila/ E1@ 25°C) – Deadmatt
Finish	Glossy, Silk Matt and Dead Matt
Colour / Shades Available	15 colors through the tinting machine plus clear
Flash point	40 °C
Thinner for Mixing and Cleaning	For Brush Application: Turpentine substitute (8300896) For Spray Application: Synthetic thinner (8300020)
VOC	405 gm/ltr.
Drying time	Touch dry - 4 to 6 hours. Recoating – 8 to 10 hours.
Coverage	8-10 m ² / Litre depending on the type of wood
Storage indication	To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.
Shelf Life	36 months from the date of production at the storage condition indicated above.
Precautions	Keep the container closed after use. Do not intermix with other products



Technical Data Sheet

Yacht PU Clear Varnish Exterior

Product Code - F65**** Series

Surface Preparation

General Instructions:

All surfaces must be clean, dry after sanding. Substrate should be free of grease, oil, dirt, fingerprints, and any contamination to ensure optimum adhesion and coating performance properties. All application and drying/curing process should be performed between 10 – 35 °C temperature and 30 – 60% RH to obtain the best finishing quality.

Health and Safety Information

Please refer to our Material Safety Data Sheet for guidance.

Disclaimer: The information in this data sheet is not intended to be exhaustive: any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to law) any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local AkzoNobel Oman SAOC representative that this data sheet is current prior to using the product.