DULUX PENETRATING PRIMER

Product Name	Dulux Penetrating Primer
Description and Usage	Dulux Penetrating primer is a solvent based acrylic primer. This alkali resistant primer has excellent penetrating properties
Benefits	• Ideal for interior and exterior applications • Excellent penetration properties • Exhibit excellent adhesion properties
Pack Size	18 Litre,3.6 Litre
Colour Range	White

Film Properties

Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

Composition (nominal)	Binder : Special Acrylic Resin Solvent : Dulux Acrylic Thinner

Product Data

Finish	Smooth / Matt
Volume Solids %	33 ± 2%
Typical WFT (microns) per coat	90 – 120 μm
Typical DFT (microns) per coat	30 – 40 μm
Theoretical Coverage	11.00 – 8.3 m^2/ litre / coat
Practical Spreading Rate	Depending on substrate, application method, application conditions and system, etc.
Specific Gravity	White 1.30 ± 0.05 kg/l

Drying / Over coating Information

° C	Touch Dry	Overcoating	Hard Dry
@ 30°c	1 hr	5 hrs	5 hrs

Application	Brush, Roller, Spray

Thinning *Brush, Roller or Spray*	5-10 % depending on the method of application with Dulux Acrylic Thinner

DULUX PENETRATING PRIMER

Cleaning Up	Clean all equipment with thinner immediately after use.
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Use suitable filler for smaller cracks and holes
System Information *New, Normal, Sound Surfaces(Steel Surface)*	Sealer (1 coat) Dulux Penetrating Primer Followed by recomended dulux paint system
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.